

AONT-1522

GPON Gateway ONT (4GE+2POTS+RF)

Feature Summary

- ◆ ITU-T G.984 compliant
- ◆ Indoor wall or table mount
- ◆ Four 10/100/1000Base-T Ethernet RJ-45 ports
- ◆ Two FXS RJ-11 ports
- ◆ One RF video port
- ◆ VoIP features: SIP, multiple voice codecs, T.38 fax, and various CLASS services
- ◆ Integrated router with features such as IPv4, IPv6, IPoE, PPPoE, NAT, DHCP, DNS, IP Filtering, IP forwarding, Static IP routing, IP QoS and Firewall
- ◆ IPv6 ready logo certified
- ◆ Built-in L2 wire-speed switch with dynamic bridging, 256 MAC addresses, 4k VLANs (802.1q tagged, untagged, port based, priority tagged, double tagged)
- ◆ ToS/DSCP to 802.1p mapping
- ◆ Flexible traffic mapping, policing and shaping
- ◆ IGMPv2/v3 snooping, proxy and filtering, 256 multicast groups
- ◆ MLD snooping
- ◆ Web based GUI for local provisioning and software upgrade
- ◆ Dual managed by ITU-T G.988 OMCI and/or remote management functions as TR-069 and Telnet for provisioning, diagnostics, monitoring, and software upgrade



Applications

The AONT-1522 has been optimized for residential homes to provide triple play services.

Advanced GPON technology

The AONT-1522 is fully FSAN (ITU-T G.984) compliant with a 1.244 Gb/s upstream and 2.488 Gb/s downstream, Class B+ GPON system.

Quality of Service

The AONT-1522 supports extensive QoS features, including 802.3x flow control, DSCP to 802.1p mapping, upstream congestion control, and downstream traffic scheduling for premium or time sensitive content. Intelligent and robust buffer and queue management for Ethernet traffic, with individually prioritized queues, ensures that tiered service offerings based on different bit-rates and QoS can be supported.

Gateway

The AONT-1522 contains both wire-speed L2 switch and L3 routing gateway with port forwarding, NAT and NAPT address translation, built-in PPPoE support for HSI, and an integrated stateful packet inspection firewall with a configurable access control list (ACL) and application-level gateway (ALG). Support for VPN (L2TP, PPTP and IPSec) pass through is also provided. Included as part of the gateway function are DHCP client, DHCP server and DNS server for IPv4 and IPv6.

Security

The AONT-1522 comes with the latest security features, including MAC address spoofing protection, MAC/IP address port binding, per-port access control list (ACL) based on port, MAC address and Ether-type, DoS prevention.

Flexible Management

The AONT-1522 is managed from the AOLT-4000 and AOLT-4200 OLT via OMCI. The AOLT in turn is managed with either Alphion Element Management System (AEMS) that provides configuration, profile based provisioning, event and fault management and performance monitoring for the AONT, or with a 3rd party NMS via northbound interface.

SPECIFICATIONS

GPON interface

Standard	Fully ITU-T G.984 compliant
Link Budget	28 dB (Class B+) ITU G.984.2 Amd1
Wavelength	transmit: 1310+/-20nm; receive: 1490+/-10nm
Line rate	Upstream: 1.244 Gb/s; Downstream: 2.488 Gb/s
Output power	+0.5 to +5.0 dBm
Sensitivity	-27 dBm (at 10 dB extinction ratio)
Overload	-8 dBm
Distance	up to 20 km (depending on split ratio and reach extension)
OLS	per ITU-T G.984.2amd2
Connector	SC/APC
TC layer	AES (128-bit key) and FEC RS(255,239)
DBA	DBRu mode 0
GEM port	up to 32
T-CONT	up to 8

Voice interface

POTS Interface	two RJ-11 connectors 5 REN per line, loop start, balanced and unbalanced ringing, country specific impedance, DTMF dialing, metallic loop testing
----------------	--

Ethernet interface

GE port Standard:	four RJ-45 connectors 10/100/1000Base-T with rate and duplex auto-negotiation and MDI/MDIX auto sensing
Flow control	per 802.3x

Power

AC adapter	input: 100-240VAC, 50/60Hz; output: 12VDC, 1.5A
Control	power on/off switch

Physical

Temperature	0 to 50 °C
Humidity	5 to 95% non-condensing
Dimension	255mm(W) x 150mm(D) x 36.5mm(H)
Weight	0.64kg
Mounting	wall or table
Power consumption	13.5 watts (max)
LEDs	Power, GPON, LOS, Internet, VoIP1-2 LAN1-4, TV

Video interface

Type	Coax F-connector
RF output level	18 dB
RF impedance	75 ohms
Total RF output	36 dBmV

Software Features

L2 Features

Bridging	802.1d transparent bridging, 256MAC table, broadcast/multicast and DLF rate limiting
VLAN	4,095 VLANs, untagged, priority tagged, port based, 802.1q tagged VLAN, 802.1ad double tagged VLAN, VLAN translation
Multicast QoS	IGMPv2/v3 snooping, 256 multicast groups 802.1p, IP ToS/DSCP to 802.1p mapping, 802.1p remarking
Scheduling	SP, WRR, WFQ
Congestion	RED, WRED

Gateway features for IPv4 and IPv6

WAN	PPPoE, DHCP client or static IP, NAT/NAPT, port forwarding, port triggering
LAN	DHCP server and relay agent, DHCP option 60, DNS relay
Routing	RIP v1/v2 and static IP routing

IPv6 support

Certification Mode	IPv6 Ready Logo certified Dual stack lite, 6rd
--------------------	---

Firewall

Type	Stateful packet inspection
Filtering	DoS attack prevention, IP source/destination filtering, TCP/UDP port source/destination filtering, MAC source filtering
ALGs	FTP, SIP, H.323, RSTP
VPN	PPTP, L2TP, IPsec pass-through
Access control	DMZ, Parental Controls

VoIP

Protocols	SIP (RFC3261), SDP (RFC2327), RTP/RTCP (RFC3550/3605), RFC2833
CLASS	caller ID, call waiting, call forwarding, call transfer, 3-way conference, etc.
Codec	ITU-T G.711 (μ & a law), G.723.1, G.729a/b, echo cancellation, voice activity detection, silence suppression and comfort noise generation
Fax	ITU-T T.30, T.38
IP address	DHCP client or static IP configuration
IOP	Proven interoperability with major soft switch and voice gateway vendors

Management

Local	Web based GUI
Remote	ITU-T G.988 OMCI, TR-069, Telnet

Regulatory compliance

Certification	CE compliant
EMC	EN55022, CISPR-22 Class B
Safety	EN60950/UL60950
Laser safety	IEC-60825-1 Class 1 laser safety per G.664
Transient Immunity	EN/IEC61000-4-4(2001) level 2 Radiated RF: EN/IEC61000-4-3(2002) level 2 Conducted RF: EN/IEC61000-4-6(2001) level 2
Surge	EN/IEC61000-4-5(2001) 0.5 KV (line) and 1.5 KV (earth)
ESD	EN/IEC61000-4-2(2001) contact level 2, air discharge level 3
Hazardous	RoHS6, WEEE