

# ASEE-1402

## Subscriber End Equipment(1GE+1Wifi 802.11 b/g/n)

### Feature Summary

- ◆ ITU-T G.984 /IEEE802.3ah compliant
- ◆ Indoor wall or table mount
- ◆ One 10/100 Base-T
- ◆ 802.11b/g/n 2Tx2R MIMO 2.4GHz Wi-Fi interface
- ◆ Integrated router with features such as IPv4, IPv6, IPoE, PPPoE, NAT, DHCP, DNS, IP Filtering, IP forwarding, Static IP routing, IP QoS and Firewall
- ◆ Supports dual software image. Holds a working image & alternative image for image rollback
- ◆ Built-in L2 switch with dynamic bridging, (802.1q tagged, untagged, port based, priority tagged, 802.1ad double tagged)
- ◆ ToS/DSCP to 802.1p (Tag Control Information bits) mapping
- ◆ Serial number or password based activation and authentication
- ◆ IGMPv2/v3 snooping, proxy
- ◆ Dual managed by OMCI and/or remote management functions as TR-069

### Applications

The ASEE-1402 has been optimized for small business and residential homes to provide data services.

### Advanced High Bandwidth GPON/EPON technology

The ASEE-1402 is fully FSAN (ITU-T G.984) compliant & IEEE 802.3ah compliant. 2.488 Gbps downstream and 1.244 Gbps upstream for GPON/ 1.25 Gbps US/DS EPON systems.

### Quality of Service

The ASEE-1402 supports extensive QoS features, including ToS/DSCP to 802.1p mapping, Traffic classification and QoS based on layer 3 and layer 4 header.prioritizable queues, ensures that tiered service offerings based on different bit-rates and QoS can be readily supported.

### Gateway

The ASEE-1402 contains both L2 switch and L3 routing gateway with port forwarding, NAT and NAPT address translation, built-in PPPoE support for HSI, and an integrated stateful packet inspection firewall and application-layer gateway (ALG). Support for VPN pass through is also provided. Included as part of the gateway function are DHCP client, DHCP server and DNS server for IPv4 and IPv6.

### Security

The ASEE-1402 comes with the latest security features, including access control list (ACL), DMZ, and wireless encryption protocols such as WEP and (WPA-PSK).

### Flexible Management

The ASEE-1402 is managed from the AOLT-4000 family via OMCI. The AOLT in turn is managed with either Alphion Element Management System (AEMS) that provides configuration, profile based provisioning, event and fault management and performance monitoring for the ASEE, or with a 3rd party NMS via northbound interface.

# SPECIFICATIONS

## GPON /EPON Uplink interface

Standard	Fully ITU-T G.984/IEEE 802.3ah compliant
Line rate	Downstream: 2.488 Gbps; Upstream: 1.244 Gbps
Connector	SC/APC, single-mode-fiber
Link Budget	Class B+ ITU G.984.2 Amd1
Wavelength	Transmit: 1310nm; Receive: 1490nm
Tx Output power	+0.5 to +5.0 dBm launch power
WBF	Support G.984.5 Blocking filter as an option
Rx Sensitivity	-27dBm
Rx Overload	-8 dBm
TC layer	AES (128-bit key), US and DS FEC
DBA	DBRu mode 0 and mode 1
GEM port-IDs	Multiple GEM Ports per device, Broadcast & Multicast GEM Port. 802.1p mapper service Profile on U/S.
T-CONT	Multiple T-CONT per device. Flexible mapping between GEM Ports and T-CONT.
Activation	Activation with automatic discovered SN and password in conformance with ITU-T G.984.3

## Ethernet interface

Type	one 10/100/1000 Base-T interface
Connector	RJ-45 connectors
Link	auto-negotiation and MDI/MDIX auto-sensing

## Wi-Fi WLAN interface

Standard	802.11b/g/n, 2.4GHz, MIMO:2x2
	Multiple SSIDs
	64 & 128 bit Wireless Encryption Protocol support (WEP)
	Wireless Protected Access support including Pre Shared Key ( WPA-PSK)
	Radio Switched on/off function support WPS

## Power

AC Adapter	Input: 100-240VAC, 50/60Hz Output: 12VDC,1A)
DC Connector	2-pin Barrel Connector
Control	Power ON/OFF pushbutton on rear
Power	less than 10W, Dying Gasp support

## Physical

Temperature	0 °C to 50 °C
Humidity (RH)	5% to 95% relative humidity
Mounting	Desktop mounting & wall mounting
LED Indicators	PWR, LOS, PON, LAN1, PHONE, WLAN
Dimension	160mm (W)x 130mm(D) x 33.8mm(H)

## OAM

Remote	standard OMCI as per ITU-T G.984.4 and G.983.2 , Compliant to TR-069, Provisioning of all services by subset of TR-098 and TR-104 Alarm and AVC report, Performance monitoring
Download	Remote software image download over OMCI as well as activation and rebooting Dual Software images with integrity check and automatic rollback

## L2 features

Bridging	802.1d bridging
Rate Limiting	Broadcast/multicast rate limiting
VLAN	VLAN Tagging/untagging per Ethernet Port VLAN Stacking(Q-in-Q) and VLAN Translation
Multicast	IGMPv2/v3 & snooping, and IGMP snooping with Proxy report
Qos	802.1p marking/re-marking; Class of service based on UNI, VLAN-ID, 802..1p bit and combination

## Gateway features

WAN	Multiple WAN interfaces support, PPPoE client, IPoE with DHCP client or static IP, NAT/NAPT, Port Forwarding
LAN	DHCP server, DNS relay, DDNS
Routing	static IP routing
Multicast	IGMP Proxy
Others	NTP, Universal Plug and Play (uPnP)
QoS	Traffic Classification and Qos based on Layer 3 and Layer 4 header

## IPv6 support

Features	Stateless Address Auto configuration (SLAAC) DHCPv6,PPPoEv6, DNSv6
----------	-----------------------------------------------------------------------

## Firewall

VPN	VPN pass-through
Access control	ACL, DMZ,

## Regulatory Compliances

Certification	CE certificate, FCC/UL compliant
---------------	----------------------------------

*The information contained herein is for informational purposes only. Technical claims listed depend on various technical assumptions. Your experience with these products may differ if you operate the products in an environment which is different from the technical assumptions. Alphion reserves the right to modify these specifications without any prior notice. Alphion makes no warranties, expressed or implied, on the information contained in this document.*